

SECTION V - HEALTH HAZARD DATA

Waterbury, Connecticut
 Hydrocyanic acid, 200 PPM. Cyclohexanone, 50 PPM
 irritant to eyes, nose, and throat
 Dizziness, headache, lack of coordination. Severe over exposure to
 vapor can cause narcosis. Eye, throat & nose irritant.
 VAPOR: Irritant and irritant to mucous
 Vapor: Remove to fresh air, give artificial respiration & oxygen if
 necessary. Liquid: remove contaminated clothing & wash affected skin
 with soap & water. Flush eyes thoroughly at least 15 minutes & con-
 sult physician.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE	CONDITIONS TO AVOID
	STABLE	SPARKS & OPEN FLAME.
(See Section VIII for stability information) STRONG OXIDIZING AGENTS.		
HAZARDOUS DECOMPOSITION PRODUCTS PEROXIDES ARE FORMED ON LONG EXPOSURE TO AIR OR OXYGEN		
HAZARDOUS POLYMERIZATION	MAY OCCUR	CONDITIONS TO AVOID
	WILL NOT OCCUR	Avoid excessive exposure to air or oxygen.

SECTION VII - SPILL OR LEAK PROCEDURES

Wipe up or take in case material is released or spilled
 Eliminate all ignition sources. Flush with water. Avoid flushing into
 confined areas. Avoid prolonged breathing of vapors. Keep liquid out
 out eyes.
 Waste disposal method
 Incinerate.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTIVE EQUIPMENT: Self-contained breathing apparatus. Positive
 pressure air line mask. As required
 VENTILATION: LOCAL EXHAUST AS REQUIRED SPECIAL
 MECHANICAL (General) OTHER
 PROTECTIVE GLOVES: PVA GLOVES EYE PROTECTION
 OTHER PROTECTIVE EQUIPMENT: Chemical safety goggles
 Axon, boots, eye bath, safety shower

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTION TO BE TAKEN IN HANDLING AND STORING
 Highly flammable. Prevent skin contact to avoid defatting action.
 OTHER PRECAUTIONS
 Use normal good personal hygiene.

Form OSHA 20
 2-1-77

JUN 1977

Form OSHA 20
 2-1-77

U.S. DEPARTMENT OF LABOR
 Occupational Safety and Health Administration
MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
 Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: **Revel Chemical Company, Inc.** EMERGENCY TELEPHONE NO: / (212) 869-4330
 ADDRESS: **10018**
 CHEMICAL NAME AND SYNONYMS: **TRIP-SEAL**
 POLYESTER FLUOROETHYLENE
 FLUOROPOLYESTER
 FLUOROPLASTIC

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES & SOLVENTS	%	TLV (umbl)	ALLOYS AND METALLIC COATINGS	%	TLV (umbl)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL		
ADDITIVES			PLATE COATING OR CORE FLUX		
OTHERS			OTHERS		
HAZARDOUS MIXTURES OR OTHER LIQUID, SOLID, OR GASES					% TLV (umbl)

SECTION III - PHYSICAL DATA

BOILING POINT (°F)		SPECIFIC GRAVITY (40°C)	1.1
VAPOR PRESSURE (mm Hg)		REFRACTIVE INDEX	1.51
VAPOR DENSITY (AIR=1)		EVAPORATION RATE	
SOLUBILITY IN WATER		APPEARANCE AND ODOR	White, flexible cord, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	PLUMBER'S LIMITS	LM	UM
EXTINGUISHING MEDIA			
SPECIAL FIRE FIGHTING PROCEDURES	Avoid inhalation of decomposition products when burned		
UNUSUAL FIRE AND EXPLOSION HAZARDS	NONE		

Form OSHA 20
 2-1-77

JUN 1977

Form OSHA 20
 2-1-77